


EB-113

Injection Quill, Non-Retractable, Basic 1" MNPT x 3/4" Solution Tube



SPECIFICATIONS

SAFETY RATING	150 psi - PVC, CPVC, PVDF 1500 psi - Alloy
CHECK VALVE	N/A
SAF-T-SEAL TIP	N/A
QUICK DISCONNECT	N/A
VALVE/PROCESS CONNECTION SIZE	1" MNPT
INLET CONNECTION SIZE	1" MNPT
SOLUTION TUBE SIZE	3/4"
SOLUTION TUBE ID (PVC, CPVC)	0.742"
SOLUTION TUBE ID (ALLOY)	0.824"
SOLUTION TUBE OD (ALL)	1.050"
(A) OPERATING LENGTH	3.50"



ORDERING INFORMATION

PVC, CPVC, and PVDF

SERIES	SOLUTION TUBE MATERIAL	INSERTION LENGTH	TIP CONFIGURATION
EB-113	<input type="text"/>	<input type="text"/>	<input type="text"/>
	P = PVC C = CPVC K = PVDF	2 = 2" 4 = 4" 6 = 6"	0 = Standard B = 45° Bevel

ALLOY

SERIES	SOLUTION TUBE MATERIAL	INSERTION LENGTH	TIP CONFIGURATION
EB-113	<input type="text"/>	<input type="text"/>	<input type="text"/>
	H = HASTELLOY C276 S = 316SS A = Alloy 20	2 = 2" 4 = 4" 6 = 6" 8 = 8" 10 = 10" 12 = 12" 18 = 18" 24 = 24"	0 = Standard B = 45° Bevel

- 1** Inlet Connection Thread
- 2** Installation Hex
- 3** Main Connection Thread
- 4** Solution Tube
- 5** Tip