


HC-075

High Corrosion Resistance Retractable Injection Quill 3/4" Valve x 3/8" Tube



SPECIFICATIONS

SAFETY RATING
250 PSI
CHECK VALVE
INTEGRATED
SAF-T-SEAL TIP
OPTIONAL
QUICK DISCONNECT
N/A
VALVE/PROCESS CONNECTION SIZE
3/4"
INLET CONNECTION SIZE
1/2"
SOLUTION TUBE SIZE
3/8"
SOLUTION TUBE ID (W/SAF-T-SEAL)
0.423"
SOLUTION TUBE ID (W/O SAF-T-SEAL)
0.493"
SOLUTION TUBE OD
0.675"
(A) OPERATING LENGTH
12.25"
(B) VALVE/GLAND LENGTH
8"
EXTRACTION LENGTH
20.25" + INSERTION LENGTH



ORDERING INFORMATION

SERIES	VALVE SIZE	VALVE MATERIAL	SOLUTION TUBE MATERIAL	INSERTION LENGTH	TIP CONFIGURATION	CHECK VALVE SEAL
HC	-	-	-	-	-	-
	075 = 3/4"	H = HASTELLOY C A = ALLOY 20 D = Duplex 2205 U = Super Duplex	H = HASTELLOY® C276 S = 316SS A = ALLOY 20 T = Titanium Gr.2	2 = 2" 4 = 4" 6 = 6" 8 = 8" 10 = 10" 12 = 12" 18 = 18" 24 = 24"	0 = Standard B = 45° Bevel CV = SAF-T-Seal, FKM CE = SAF-T-Seal, EPDM SAF-T-Seal tip not available with Titanium solution tube material.	V = FKM E = EPDM K = KALREZ 6375

TECH NOTES

1. Check valve spring cracking pressure is 10 PSI.
2. Materials availability is subject to change. Please inquire prior to selection.
3. Length dimensions may vary depending on materials selection.
4. Standard and bevel tipped solution tubes are S40 by default. S80 is required when selecting the SAF-T-Seal tip option. With the exception of titanium tube materials, S80 is available upon request.