


# HC-300

## High Corrosion Resistant Retractable Injection Quill 3" Valve x 2-1/2" Tube



### SPECIFICATIONS

SAFETY RATING	250 PSI
CHECK VALVE	OPTIONAL
SAF-T-SEAL TIP	N/A
QUICK DISCONNECT	N/A
VALVE/PROCESS CONNECTION SIZE	3"
INLET CONNECTION SIZE	2-1/2"
SOLUTION TUBE SIZE	2-1/2"
SOLUTION TUBE ID	2.469"
SOLUTION TUBE OD	2.875"
(A) OPERATING LENGTH	23"
(B) VALVE/GLAND LENGTH	17"
EXTRACTION LENGTH	40" + INSERTION LENGTH



### ORDERING OPTIONS

SERIES	VALVE MATERIAL	SOLUTION TUBE MATERIAL	INSERTION LENGTH	TIP CONFIGURATION	CHECK VALVE SEAL
HC-300					
	H = HASTELLOY C A = ALLOY 20 D = DUPLEX 2205 U = SUPER DUPLEX	H = HASTELLOY® C276 S = 316SS A = ALLOY 20 T = Titanium Gr.2	2 = 2" 4 = 4" 6 = 6" 8 = 8" 10 = 10" 12 = 12" 18 = 18" 24 = 24"	0 = Standard B = 45° Bevel DH = Diffuser Holes	00 = No Check Valve 05 = Alloy, FKM 06 = Alloy, EPDM

### TECH NOTES

- When selecting alloy check valves options, the body material of the check valve is the same as the solution tube material.
- Diffuser hole configurations to be determined by customer. SAF-T-FLO does not provide recommendations regarding diffuser hole layouts.
- Materials options are subject to change. Consult factory prior to selection.
- Length dimensions may vary depending on specific materials combinations.