

KH - Pump Performance Chart

Model	SPM @ 1750 rpm	Capacity @ 60 Hz		Pressure *		Connection		Motor
		GPH	LPH	PSI	BAR	NPT/BPT	Flange	
KH-22	20	1.5	6	300(150)	20(10)	1/2"	1/2"	1/2 Hp
	31	2.4	9	300(150)	20(10)	1/2"	1/2"	1/2 Hp
	46	3.5	13	300(150)	20(10)	1/2"	1/2"	1/2 Hp
	60	4.9	18	300(150)	20(10)	1/2"	1/2"	1/2 Hp
	76	6.1	23	300(150)	20(10)	1/2"	1/2"	1/2 Hp
	92	7.9	30	300(150)	20(10)	1/2"	1/2"	1/2 Hp
	106	9.0	34	300(150)	20(10)	1/2"	1/2"	1/2 Hp
	121	10.9	41	300(150)	20(10)	1/2"	1/2"	1/2 Hp
	138	12.4	47	300(150)	20(10)	1/2"	1/2"	1/2 Hp
KH-35	20	3.8	14	300(150)	20(10)	1/2"	1/2"	1/2 Hp
	31	5.8	22	300(150)	20(10)	1/2"	1/2"	1/2 Hp
	46	8.6	33	300(150)	20(10)	1/2"	1/2"	1/2 Hp
	60	12	45	300(150)	20(10)	1/2"	1/2"	1/2 Hp
	76	15	57	300(150)	20(10)	1/2"	1/2"	1/2 Hp
	92	19	73	300(150)	20(10)	1/2"	1/2"	1/2 Hp
	106	22	84	300(150)	20(10)	1/2"	1/2"	1/2 Hp
	121	27	101	300(150)	20(10)	1/2"	1/2"	1/2 Hp
	138	31	116	300(150)	20(10)	1/2"	1/2"	1/2 Hp
KH-57	20	10	39	300(150)	20(10)	1/2"	1/2"	3/4 Hp
	31	16	59	300(150)	20(10)	1/2"	1/2"	3/4 Hp
	46	23	87	300(150)	20(10)	1/2"	1/2"	3/4 Hp
	60	32	122	300(150)	20(10)	1/2"	1/2"	3/4 Hp
	76	40	153	300(150)	20(10)	1/2"	1/2"	3/4 Hp
	92	52	196	256(150)	18(10)	1/2"	1/2"	3/4 Hp
	106	60	226	242(150)	17(10)	3/4"	1"	3/4 Hp
	121	72	272	200(150)	14(10)	3/4"	1"	3/4 Hp
	138	82	311	170(150)	12(10)	3/4"	1"	3/4 Hp
KH-82	20	21	81	240(150)	17(10)	3/4"	1"	3/4 Hp
	31	33	124	240(150)	17(10)	3/4"	1"	3/4 Hp
	46	48	182	215(150)	15(10)	3/4"	1"	3/4 Hp
	60	67	254	170(150)	12(10)	3/4"	1"	3/4 Hp
	76	84	320	140(140)	10(10)	3/4"	1"	3/4 Hp
	92	108	410	130(130)	9(9)	1"	1"	3/4 Hp
	106	125	472	115(115)	8(8)	1"	1"	3/4 Hp
	121	150	567	100(100)	7(7)	1"	1"	3/4 Hp
	138	171	649	85(85)	6(6)	1"	1"	3/4 Hp

* - XX(xx) Pressure rated for SS (PVC / PVDF)



